

QuadroMAX®

Universal, Scalable Outdoor Lighting Fixture





Mounting Options



Wattage Configurations



Categories of Lighting



Sleek Body









UNIVERSAL APPEAL

Meet QuadroMAX, a single fixture that can be scaled across four main categories of outdoor lighting (Area, Flood, Wall Pack, Canopy) and multiple applications. Using eight different mounting arms, the fixture can be customized into virtually any type of outdoor fixture.
















20kV SURGE SUPPRESSOR



COMPLETE PHOTOMETRIC DISTRIBUTION



10-YEAR WARRANTY



WARM TO COOL COLOR TEMPS



DLC PREMIUM LISTED



THREE FINISHES



WIDE RANGE OF EQUIVALENCIES



MaxLite gives you one convienient way to order your QuadroMAX with two easy steps.



Choose Your Light Engine and Optional Sensor

The QuadroMAX fixture can be scaled up or down according to your project needs, so you receive a fixture that is sized right for the wattage, the application and your budget.



6,090 lm **Equivalent to: 150W HID**

9,060 lm **Equivalent to:** 250W HID

12,290 lm **Equivalent to:** 320W-400W HID

15,255 lm **Equivalent to: 400W HID**

Equivalent to: 400W HID

Order Example: QM-5AU7T350N-B-BPC

FAMILY	_	LED ENGINES		DRIVER		DRIVER		DISTRIB.		ССТ		MOUNT OPTIONS		_	FINISH		_	OCCUPANCY & PHOTOCELL OPTIONS	
QM=	_	2A=	24 LEDs (55W) 6000-6300 lm	U=	120-277V	7=	700mA	T2=	Type II	30=	3000K	N=	None	-	В=	Bronze	1	(OMIT)=	None
		3A=	36 LEDs (80W) 9000-9300 lm	н=	347-480V**	8=	800mA**	тз=	Type III	40=	4000K	C=	Canopy		w=	White		MS4=	Sensor (Hi/Low/Off)
		4A=	48 LEDs (110W) 12,000-12,600 lm					T4=	Type IV	50=	5000K				L=	Black		RPC=	NEMA Rotatable Photocell Receptacle (std.)
		5A=	60 LEDs (135W) 14,800-15.500 lm					T5=	Type V									PR5=	Photocell Receptacle 5-Pin
		6A=	72 LEDs (160W or 185W)* 17,800-20,000 lm															PR7=	Photocell Receptacle 7-Pin
																		врс=	Button Photocontrol

Depends on Drive Current **5-Year Limited Warranty

Choose Your Mounting Options



Rigid Pole Mount



Slipfitter Knuckle



Slipfitter Fixed



Fixed Surface



Knuckle Surface



Trunnion Swivel



Wall Pack





Canopy Mount

Order Example: QM-SK-B FAMILY MOUNTING FINISH Rigid Pole Mount B= Bronze Slipfitter Knuckle SK= Slipfitter Fixed FS= Surface

W= White L= Black Knuckle Surface Swivel WP= Wall Pack

Canopy mount included with fixture if selected. Not sold separately.

Church Converts to **Energy Saving Benefits of** LED Lighting from MaxLite

The First Baptist Church of Bethalto, Illinois was looking to update its facility with improved lighting that provided energy savings. The 25,000-square-foot building and exterior were lit by an aging system of fluorescent and metal halide fixtures that had become prohibitively expensive and labor intensive to maintain. Converting to LED was the ideal solution because of its lower energy consumption and longevity. Working with local representative agency Cool City Lights, the church replaced the lighting throughout the property with MaxLite LED lamps and fixtures.

The most dramatic transformation occurred on the exterior of the building, where many of the fixtures were no longer functional. Six 400-watt metal halide pole-top fixtures in the parking lot were replaced with QuadroMAX, MaxLite's universal and scalable outdoor luminaire, in a 160-watt, 5000K configuration. Delivering exceptional efficacy of 110 lumens per watt, QuadroMAX can be customized for virtually any type of outdoor lighting application by applying one of eight different mounting arms to a universal body to create a canopy, area, flood or wall pack luminaire.





'We were very pleased with the lighting upgrades. The biggest improvement was in the parking lot. Previous dark spots have been eliminated, and the safety of those coming and going from the Church has improved."

- Tom Howland, Trustee, **First Baptist Church**

Use QuadroMAX for virtually any type of outdoor lighting application.



Area Light



Flood Light



Wall Pack



Canopy



12 York Ave. West Caldwell, NJ 07006 T: 1-800-555-5629 F: 973-244-7333

www.maxlite.com



Quickest Turnarounds

We keep the QuadroMAX in stock and just add the mounting part you need. This means customers can order a specification-grade. customizable fixture that ships in the same amount of time as a standard product.



Best-In-Class Protection

The QuadroMAX is engineered with state-of-theart LEDs and 20KV surge suppression to protect the fixture from power surges. A maintenancefree lifetime of 100,000 hours, limited ten-year warranty and lifetime customer support make the QuadroMAX the smart choice for converting lighting systems to the energy- and cost saving benefits of LED.